TOE JACKS JACKS

Simplex Toe Jacks Are The Heavy Haulers & Structural Movers First Choice.





Heavy equipment movers have long realized the benefits of Simplex toe jacks. Truly a universal tool, hydraulic toe jacks can do a wide variety of jobs faster & safer than standard jacks. With toe heights starting at 25,4mm and capacities up to 25 tons, Simplex hydraulic toe jacks are the first choice for transformer maintenance, heavy hauling, structural moving, and rigging.



- 8 Models
- Self-contained or remote models for maximum versatility.
- Low toe heights fit in tight clearances.
- The lowest handle effort for easy operation.
- The lowest weights for reduced back injuries.
- Swivel sockets for access in close quarters. (TJH5 & TJH10 Only)
- New light weight TJH109LS and TJH105A

Toe Jacks

	Model Number	Cap. (tons)		Minimum Height		Base Area	Max. Handle Effort	Method Of	Weight (kg)
	real liber	((0113)	()	Toe (mm)	Cap (mm)	(mm)	(kg)	Return	(Ng)
ĺ	TJH2	2	113	16	235	125 x 178	23,2	Load	8,2
Ì	TJH5	5	117	25	298	184 x 270	15,0		24,1
ı	TJH10 TJH109	10	149	32	333	241 x 286	17,3		38,6
١			229	57	559	165 x 254	36,4	Spring	25,5
	TJH105A		127	55	397	152 x 229	33,2		16,8
1	TJH109LS		229	51	410	152 x 241	33,2		18,6
١	TJA25	25	165	57	349	241 x 305	45,5	Load	59,1



TJH109LS

Note: Handles Are Included With All Self-Contained Models.

Toe Jacks - Remote

Model		Stroke (mm)	Minimum Height			Res.	Pres. @ Cap.	Туре	Weight (kg)
Number	(tolls)		Toe (mm)	Cap (mm)	Area (mm)	Cap. Reqd. (cm³)	(bar)		(Ng)
TJR109	10	229	57	562	165 x 254	868,7	448,5	S/A Spring Return	20,5

Note: To use Simplex Remote Jack with existing pumps or hoses, order Coupling Adaptor #85383 separately.